



Specifications

System	
Front I/O	Mini-USB x 1, Line-out x 1, DVI/VGA input x 1, RJ-45 x 1, LED x 2, Button (SW18SW2) x 2
Rear I/O	DIP Switch
OS support	Windows® XP, Windows® 7
Mechanical	
Construction	Steel front bezel & chassis
Mounting	Wall/ Desktop/ VESA 75/100
Dimension	—
Carton Dimension	—
Gross Weight	—
Net Weight	—
Environmental	
Operating Temperature	32°F ~ 122°F (0°C ~ 50°C)
Storage Temperature	-4°F ~ 140°F (-20°C ~ 60°C)
Storage Humidity	10%~95% @ 40°C; non-condensing
Vibration	1 g rms/ 5~500Hz/ Random operation
Shock	15 G peak acceleration (11 msec. Duration)
EMC	CE/FCC Class A
Power Supply	
DC input	12V DC w/ power adapter

Note: Users have to select the Remote Display to work with the ACG-203

Features

- Supports Remote Display Function
- Easy-To-Install: RJ-45 Cable x 1
- Easy-To-Deploy: TCP/IP Protocol Support
- Desktop/ VESA Mount



Ordering Information

- **TF-ACG-203-A1-1010**
Remote Display Host Gateway w/One to Multiple Networks)
- **TF-ACG-203-A2-1010**
Remote Display Host Gateway w/One to One Network)

Optional Accessories

- TBD