


EMB-945T Rev. A

Embedded Motherboard With Intel® Core™ 2 Duo/ Core™ Duo/ Celeron® M Processor



Features

- Socket-478M Intel® Core™ 2 Duo/ Core™ Duo/ Celeron® M Processor
- Intel® 945GME + ICH7M
- SODIMM DDR2 400/533/667 Max. 4 GB
- Gigabit Ethernet x 1 (Marvell® 88E8053)
- Up To 24-bit Dual-channel LVDS LCD
- AC97 5.1CH Audio
- Type 2 CompactFlash™ x 1, SATA 1.5Gb/s x 2 (Optional RAID 0 & 1), EIDE x 1
- COM x 6, Parallel x 1, USB2.0 x 6, 8-bit Digital I/O x 1
- PCI x 1, PCI-Express [x1] x 1 And Mini PCI x 1
- ATX



Specifications

System	
Form Factor	Mini-ITX
Processor	Supports Socket-478M Intel® Core™ 2 Duo/ Core™ Duo/ Celeron® M Processor up to 2.16 GHz, FSB 533/667
System Memory	200-pin DDR2 SODIMM x 2, Max. 4 GB (DDR2 400/533/667)
Chipset	Intel® 945GME + ICH7M
I/O Chipset	ITE 8712 + Fintek F81216D
Ethernet	Marvell® 88E8053, 10/100/1000Base-TX, RJ-45 x 1
BIOS	Award Plug & Play BIOS – 512 KB ROM
Wake On LAN	Yes
Watchdog Timer	ITE 8712
H/W Status Monitoring	Supports power supply voltages, fan speed and temperature monitoring
Expansion Interface	Mini PCI x 1, PCI x 1, PCI-Express [x1] x 1
Power Requirement	ATX (+3.3V, +5V, +12V)
Power Consumption (Typical)	T7400 2.16 GHz, DDR2 667 1 GB 2.59A@+12V, 2.88A@+5V, 0.6A@+3.3V
Board Size	6.7"(L) x 6.7"(W) (170 mm x 170 mm)
Gross Weight	1.2 lb (0.5 Kg)
Operating Temperature	32°F ~ 140°F (0°C ~ 60°C)
Storage Temperature	-40°F ~ 176°F (-40°C ~ 80°C)
Operating Humidity	0% ~ 90% relative humidity, non-condensing
MTBF (Hours)	70,000
Display	
Chipset	Intel® 945GME
VGA/LCD Controller	1. Intel® 945GME integrated Graphics, shared memory up to 224 MB with DVM; LCD supports up to 24-bit dual-channel LVDS 2. Chrontel 7307 for DVI support 3. Chrontel 7308 for 24-bit dual-channel LVDS support
DVI	DVI-D in pin-header
I/O	
Storage	EIDE x 1 (UDMA 33 for one device), SATA 1.5Gb/s x 2, Type 2 CompactFlash™ x 1
Serial Port	RS-232 x 5, RS-232/422/485 x 1
Parallel Port	SPP/ EPP/ ECP mode
USB	USB2.0 x 6
PS/2 Port	Keyboard x 1, Mouse x 1
Digital I/O	Supports 8-bit (Programmable)
IrDA	One IrDA Tx/Rx header
Audio	Mic-in, Line-in, Line-out, S/PDIF in/out


Packing List

- **1701440500**
44-pin ATA33 Cable
- **1700200200**
DVI Cable
- **1709100201**
USB Cable
- **1701100206**
Serial Port Cable
- **9657666600**
Jumper Cap
- **1709070500**
SATA Cable
- **1702150150**
SATA Power Cable
- **M166666006**
CPU Fan, Box 60 x 25.4 mm, for Socket-478M
- **M20852T000**
Metal I/O Bracket
- **Product CD**
- **EMB-945T Rev.A**

EMB-945T Rev. A

Dimension

Unit: mm



Ordering Information

Part Number	CPU	RAM	Fan/Fanless	Display	Storage	LVDS	LAN	USB	RS-232	RS-232/422/485	Expansion Slot	Power	Temp.
TF-EMB-945T-A10	Socket	SODIMM	Fan	VGA/LVDS/DVI-I	SATA2 x 2, EIDE x 1, CF x 1	24-bit Dual-channel	GbE x 1	6	5	1	PCI-E[x1] x 1 Mini PCI x 1 PCI x 1	ATX	0°C ~ 60°C

Optional Accessories

- TF-PER-R04P-A11**
 Riser Card, PCI + PCI-Express [x4] for EMB-945T Rev.A
- TF-PER-C10L-A10**
 Mini PCI 10/100Base-TX Ethernet Module with Realtek 8100C
- TF-PER-C10L-A10-01**
 Mini PCI Gigabit Ethernet Module with Realtek 8110S
- TF-PER-C10L-A10-03**
 Mini PCI Gigabit Ethernet Module with Intel® 82541GI
- TF-PER-C20S-A10**
 Mini PCI 2-port SATA Module Rev. A1.0
- TF-PER-C30F-A10**
 Mini PCI 3-port IEEE 1394a Module
- TF-PER-1110-A10**
 Riser Card for PCI, 2-slot
- TF-PER-C102**
 PCI-Express Dual Ethernet Board
- 1700200200**
 DVI Cable
- 17592SPI30**
 Cooler