



Specifications

System	
Form Factor	PC/104
Processor	Intel® Atom™ N450 1.66 GHz Processor
System Memory	Onboard DDR2 667, Max. 1 GB
Chipset	Intel® ICH8M
I/O Chipset	SCH3114
Ethernet	Intel® 82567V for 10/1000/1000Base-TX
BIOS	AMI BIOS – 4 MB Flash
Wake on LAN	Yes
Watchdog Timer	Generates a time-out system reset
H/W Status Monitoring	Supports Power Supply Voltage, Fan Speed and Temperature Monitoring.
Expansion Interface	PCI-104, Mini Card
Battery	Lithium battery
Power Requirement	12V
Power Consumption (Typical)	Intel® Atom™ N450 1.66GHz, DDR2 667 1 GB 1.3A@+12V
Board Size	3.55" x 3.77" (90mm x 96mm)
Gross Weight	0.35 lb (0.16 Kg)
Operating Temperature	32°F ~ 140°F (0°C ~ 60°C)
Storage Temperature	-40°F ~ 176°F (-40°C ~ 80°C)
Operating Humidity	0% ~ 90% relative humidity, non-condensing
MTBF (Hours)	83,000
Display	
Supports CRT/LCD simultaneous/ dual view displays	
Chipset	Intel® Atom™ N450 processor integrated
Memory	Shared system memory up to 384 MB/ DVMT 4.0
Resolutions	Up to 1400 x 1050 for CRT Up to 1280 x 768 for LCD
LCD Interface	18-bit single channel LVDS
I/O	
Storage	SATA 3.0Gb/s x 1, Type 1 CompactFlash™ x 1
Serial Port	RS-232 x 3, RS-232/422/485 x 1
Universal Serial Bus	USB2.0 x 4
PS/2 Port	Keyboard + Mouse x 1

Features

- Intel® Atom™ N450 1.66 GHz Processor
- Intel® ICH8M
- Onboard DDR2 667 Memory, Max. 1 GB
- Gigabit Ethernet x 1
- CRT, 18-bit Single Channel LVDS LCD
- SATA 3.0Gb/s x 1, CompactFlash™ x 1
- USB2.0 x 4, COM x 4
- PCI-104, Mini Card Expansion Interfaces
- +12V Only Operation



Packing List

- 965766600
Jumper Cap
- 17592LNP00
Heatshink
- Product CD
- PFM-LNP with Cooler

