

ED3141 Series

Hardened 10/100BASE-TX Ethernet Extender



Value

- Specific design for industrial communication applications with UL508 safety certification
- ISA 12.12.01 (UL1604) Certified for Class I, Division 2 Classified for use in hazardous locations
- Alternative long-distance Ethernet solution to reduce infrastructure cost and shorten the project schedule by using existing copper wires

Features

- Complies with NEMA TS1 & TS2 Environmental requirements for Traffic control equipment
- Complies with IEC61000-6-2 EMC Generic standard immunity for Industrial environment
- Operates transparent to higher layer protocols such as TCP/IP
- Ethernet Port: 10/100Mbps-Full/Half-duplex, Auto-Negotiation, Auto-MDI/MDIX
- Support DIP switch to select Local or Remote side
- Ethernet Extender (RJ-11 and Terminal Block) Port: Symmetrical on the VDSL, High-speed Full-duplex 50Mbps communications link over existing copper telephone wire
- Ten speeds with speed indicator LEDs on front panel of unit,
 - . Up to 50Mbps @ about 300meters (984ft.),
 - . 1Mbps @ about 1,900meters (6,232ft.)
- Redundant power inputs with Terminal Block and DC Jack
- -40°C to +75°C (-40°F to 167°F) operating temperature range
- Hardened aluminum case
- Supports DIN-Rail , Panel, and Rack Mounting installation

Ordering Information

ED3141-00B Hardened 10/100BASE-TX Ethernet Extender

Power Supply : (Optional)

*Option A - The Terminal Block type external power supplies are not included. Please order the following part numbers:
DR-30-24, DR-60-24, DR-75-24, DR-120-24 or 41-136046-X (X)=1: US, 2: EU, 3: UK, 4: AU, 5: JP

**Option B - The external power adapters and power cords are not included. Please order the following part numbers:
41-136044-X (X)=1: US, 2: EU, 3: UK, 4: AU, 5: JP

Installation Type : Optional Panel mount kit, part number: KP-AA96-480

Specifications

Technology	
Standards	IEEE802.3 10BASE-T, IEEE802.3u 100BASE-TX, IEEE802.3x, Ethernet over VDSL
Protocols	Transparent to higher layer protocols
Processing Type	Half-duplex back-pressure and IEEE802.3x Full-duplex flow control
Power	
Input	Input Voltage: 12 to 30VDC (Terminal Block); 12VDC (DC Jack)
Power Consumption	4.2W Max. 0.35A @ 12VDC, 0.175A @ 24VDC
Overload Current Protection	Present
Reverse Polarity Protection	Present
Mechanical	
Casing	Aluminum case IP30
Dimensions	50mm (W) x 110mm (D) x 135mm (H) (1.97" (W) x 4.33" (D) x 5.31" (H))
Weight	0.8Kg (1.76lbs.)
Installation	DIN-Rail (Top hat type 35mm), Panel, Rack Mounting
Interface	
Ethernet Port	PPort: One RJ-45 port, 10/100BASE-TX Full/Half-duplex Auto-Negotiation, Auto-MDI/MDIX PoE Port: complies with IEEE802.3af and IEEE802.3at standard Speed: 10/100Mbps Distance: 100meters (328ft.) Cable: 10BASE-T: UTP CAT. 3, 4, 5 (2-pair wire) 100BASE-TX: UTP CAT. 5 (4-pair wire)
Ethernet Extender Port	Port: One RJ-11 and Terminal Block port Speed: 1/3/5/10/15/20/25/30/40/50Mbps Distance: 1900meters (6,232ft.) Cable: Telephone wire 24 AWG (0.5mm diameter, 1-pair wire) or larger
DIP switch	One DIP Switch: Local (CO) or Remote (CPE)
LED Indicators	Per Unit: Power Status (Power) Per Port: 10/100TX: Link/Activity, Full-duplex Line: Error, Link, Local, Remote

Environment	
Operating Temperature	-40°C to +75°C (-40°F to 167°F)
Storage Temperature	Tested @ -40°C to +85°C (-40°F to 185°F)
Ambient Relative Humidity	5% to 95% (non-condensing)
Regulatory Approvals	
ISO Safety	Manufactured in an ISO9001 facility UL508 ISA 12.12.01, Class I, Division 2 Classified for use in hazardous locations
EMI	*FCC Part 15, Class A *EN61000-6-3 - EN55022 - EN61000-3-2 - EN61000-3-3
EMS	*EN61000-6-2 - EN61000-4-2 (ESD Standards) Contact: + / - 4KV; Criteria B Air: + / - 8KV; Criteria B - EN61000-4-3 (Radiated RFI Standards) 10V/m, 80 to 1000MHz; 80% AM Criteria A - EN61000-4-4 (Burst Standards) Signal Ports: + / - 4KV; Criteria B D.C. Power Ports: + / - 4KV; Criteria B - EN61000-4-5 (Surge Standards) Signal Ports: + / - 1KV; Line-to-Line; Criteria B D.C. Power Ports: + / - 0.5KV; Line-to-earth; Criteria B - EN61000-4-6 (Induced RFI Standards) Signal Ports: 10Vrms @ 0.15 - 80MHz; 80% AM Criteria A D.C. Power Ports: 10Vrms @ 0.15 - 80MHz; 80% AM Criteria A - EN61000-4-8 (Magnetic Field Standards) 30A/m @ 50, 60Hz; Criteria A
Environmental Test Compliance	*IEC60068-2-6 Fc (Vibration Resistance) 5g @ 10 - 150Hz, Amplitude 0.35mm (Operation/Storage/Transport) *IEC60068-2-27 Ea (Shock) 25g @ 11ms (Half-Sine Shock Pulse; Operation) 50g @ 11ms (Half-Sine Shock Pulse; Storage/Transport) *IEC60068-2-32 Ed (Free Fall) 1M (3.281ft.)

Dimensions

